



CODE	L(mm)
N12UFD4EU20ES	500 ±50
N12UFD4EU21ZS	1000 ±50
N12UFD4EU22ZS	2000 ±50
N12UFD4EU22ES	2500 ±50
N12UFD4EU23ZS	3000 ±50
N12UFD4EU25ZS	5000 ±1%
N12UFD4EU27ZS	7000 ±1%
N12UFD4EU210S	10000 ±1%
N12UFD4EU215S	15000 ±1%
N12UFD4EU220S	20000 ±1%

Cable Data		Marking		Connection layout		Housing Data		Description:		
 Dim. in mm		Conductors Material: Electrolytic bare copper	Text:	VISTA A 		Standard: IEC 61076-2-101	Customer: Customer code: Code: N12UFD4EU2XXS			
Composition: 4 x AWG24	Lot description:	Shielding: 14 x 0,15	Color:			Rated Voltage: 250 V				
Shield:		Character height:	Rated Current: 4 A							
Insulation Material: SRPVC Style 1061	Marking position:	Marking step:	Insulation: ≥100MΩ (IEC60512)			Contact resistance: ≤10mΩ				
Jacket Material: PVC Style 2464	UL AWM 758 CSA C22.2	Color: Black (RAL 9005)	Character height:	Fixing screw torque: min 0,5; max 0,8 N/m	Temperature range: -25°C...+80°C	Housing Color: Black	Protection Class: IP67	Contact Material: CuSn gold plated	Mounting: Anti-vibration system	Overmoulding material: TPU V0 (Polyurethane)
Jacket Color:	Marking step:	Marking step:	Marking step:	1 Brown 2 White 3 Blue 4 Black	Housing Color: Black	Contact holder material: PA +GF V0	Drawn: Giudice C.	Approved: Giudice C.	Draw no.: 20412	
					Standard: IEC 61076-2-101	Date: 15/10/2020	Revision date:	Revision no.: 0		

This drawing can not be copied or reproduced in any way and can not be passed to third parts without written authorization.

MCA
CONNECTORS
MCA Connectors S.r.l.
Via Plebiscito, 150
73058 TUGLIE (LE)
Tel.: 0833 518248
Fax.: 0833 395926
mail: info@mcaconnectors.com
web: www.mcaconnectors.com